

300487

2021-060

123027



2

()

Ga

23

80%~85%

90%

2006

				□□ □□
				□□ □□
				□□ □□
				□□ □□

2008

70 4N

250

2012

2016

3,376.61

2012

40t/a

2014 7

10,051.88

2008 2012

2012

2020	2021	1-3	7,996	2,740
			7,135	

ASTM

ASTM

Parameter	Type E.1	Type E 1.1	Type E 1.2	Sunresin
Application	PCP LED	OLED	Mircons	OLED/Mircons
Resistivity, 25 (M .cm)	18.1	18.2	18.2	18.2
TOC (µg/L)(on-line)	5	2	1	0.45~0.70
Dissolved oxygen (µg/L)	25	10	3	0.9
On-line particles /L(micron range)				
0.05-0.1	-	1000	200	30-50
0.1-0.2	1000	350	<100	10-25
Silica Dissolved (µg/L)	3	1	0.5	0.10-0.12
Anions and Ammonium (µg/L)	0.1	0.1	0.05	<0.05
Metals by ICP/MS (µg/L)	0.05	0.02	0.005	<0.005

ASTM

Vulkan 9

6

SQM

Ansson

		<input type="checkbox"/>		

2019


8900

65% 35%

2009

2019

241



1

2

3

4

	2020	2021	1-3		45	167	
0.05%	0.57%		22	129			0.05%
0.89%				6,446			

65%

-

		Cytiva	GE	Bio-rad
Tosoh	Merck			



60 ~ 250 um

2021 4 28

6

--	--	--	--	--	--

5 13

	2019 54% 60%
	50

M' 1yQ 1 N•kÜ i

	“ ‘ ’	VOCs	10%	”
	VOCs		2020	
		2030		2060

21

000408.SZ		91%	40.6	179.5	5.0
600499.SH		26%	33.6	90.1	4.2
300272.SZ		1%	36.7	140.6	3.2
300070.SZ		5%	347.8	20.6	1.1

5 24 —2021 6 24

5%

5%

5%

3

1 2021

1

3

1 19			_____
3 23			_____
4 27			_____
4 27			_____
4 27			_____
6 7			_____
6 6			_____

5 13			_____ _____ _____
5 31			_____ _____ _____ _____
6 16			_____ _____

2021 7 9